

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

Claim 1 (previously presented): A powder coating composition extruder comprising:

one or more rotating screws;

a plurality of adjacent segments surrounding the rotating screw(s), each of the segments including a cooling system for cooling material in the segment, and a heating system for heating material in the segment, wherein the cooling system and the heating system of each of the segments can be selectively, independently operated, one of the segments having an inlet for receiving a base material comprising at least one component of a thermosetting powder coating composition into the extruder and one of the segments having an outlet for discharging material from the extruder;

a source of the base material in flow communication with the inlet;

a source of one or more hard to incorporate particulate additives;

and

an additive injector in flow communication with the source of hard to incorporate particulate additives for injecting the one or more hard to incorporate particulate additives into at least one segment at an injection position at the inlet or between the inlet and the outlet, wherein the injector includes a low pressure vessel, and a flow regulator between the low pressure vessel and the injection position, a source of pressurization coupled to the low pressure vessel for pressurizing the low pressure vessel, and ~~a mechanism~~ means for maintaining the pressure in the low pressure vessel less than about 100 PSI when the hard to incorporate particulate additives are injected into the at least one segment containing the base material, ~~wherein the extruder is suitable for use in a method of making powder coatings at a pressure of less than about 100 PSI.~~

Claims 2-4 (canceled)

Claim 5 (previously presented): The extruder of Claim 1, wherein each cooling system includes a cooling fluid inlet and outlet in each segment.

Claim 6 (previously presented): The extruder of Claim 1, further including a pre-mix hopper and a mechanical feeder extending from an exit of the pre-mix hopper to the inlet of the extruder.

Claim 7 (Withdrawn): A low pressure liquid additive injector for an extruder comprising:

- a low pressure vessel;
- a source of pressurization coupled to the pressure vessel;
- a mechanism for maintaining the pressure in the pressure vessel less than about 100 PSI;
- a flow regulator coupled to the pressure vessel; and
- an injector outlet downstream of the flow regulator.

Claim 8 (Withdrawn): A powder coating composition extruder system with dynamic additive control comprising:

- a pre-mix hopper adapted to hold a base material;
- one or more rotating screws;
- a plurality of adjacent segments surrounding the rotating screw(s), each of the segments including a fluid cooling system for cooling material in the segment, and a heating system for heating material in the segment, wherein the cooling system and the heating system of each of the segments can be selectively, independently operated, a first segment having a main inlet for receiving material from the pre-mix hopper and a final segment having an outlet for discharging material from the extruder;
- a low pressure additive injector for injecting one or more liquid additive(s) into one or more chambers at a position at the main inlet or between the main

inlet and the outlet, wherein the additive injector includes a low pressure vessel, a source of pressurization coupled to the pressure vessel, a mechanism for maintaining the pressure in the pressure vessel less than about 100 PSI, a flow regulator coupled to the pressure vessel, and an injector outlet downstream of the flow regulator; and
a monitor adjacent the outlet monitoring the characteristics of the coating composition and coupled to a controller for the additive injector.

Claim 9 (Withdrawn): The extruder system of Claim 8, wherein each cooling system includes a cooling fluid inlet and outlet in each segment, and each heating system includes a heating element.

Claim 10 (Withdrawn): The extruder system of Claim 8, further including a mechanical feeder extending from an exit of the pre-mix hopper to the main inlet.

Claim 11 (Withdrawn): The extruder system of Claim 10, including a single motor driving the rotating screws and the mechanical feeder.

Claim 12 (Withdrawn): The extruder system of Claim 8, wherein the position at which injection occurs is spaced along the extruder system at least one segment from the main inlet.